

GS Models - silniki trójfazowe

Typ silnika	KV obroty/min/V	Ilość celi Li-Po	Średnica wału (mm)	Zalecane śmigło	Maksymalna moc [W]	Maksymalny ciąg [g]	Masa silnika [g]	Masa modelu (g)
GB2433-3250	3250	2-4	3		315		65	
GB2445-3350	3350	2-4	3		450		97	
GB2835-2650	2650	3-6	4		620		98	
GC2220-1780	1780	2-3	2	GWS 8x4.3 / 8x4	120	600	28	200-500
GC2826-1260	1260	2-3	3,175	GWS 8x4 / APC 9x4.7	220	600	45	250-500
GC2826-1450	1450	2-3	3,175	GWS 8x5 / APC 7x4	240	600	45	250-500
GC2830-700	700	2-4	3,175	APC 10x4.7 / 11x3.8	220	900	57	400-800
GC2830-910	910	2-4	3,175	APC 10x4.7 / 10x5	260	900	57	400-800
GC2834-1120	1120	2-4	3,175	APC 10x5 / 9x4.5 / 10x4.7	380	1200	67	550-1100
GC2834-880	880	2-5	3,175	APC 11x5.5 / 12x6	340	1200	67	550-1100
GC3530-1330	1330	2-4	4	APC 10x5 / 9x4.5 / 10x4.7	350	1500	78	750-1400
GC3530-950	950	2-4	4	APC 11x5.5 / 12x6	310	1500	78	750-1400
GC3536-1250	1250	2-4	4	APC 11x5.5	680	2600	109	1400-2500
GC3542-1100	1100	2-4	4	APC 11x7 / 11x3.8 / 12x6	850	2600	132	1400-2500
GC3542-810	810	2-4	4	APC 12x6	660	2600	132	1400-2500
GC3542-930	930	2-4	4	APC 11x5 / 10*5	750	2600	132	1400-2500
GC4250-720	720	3-5	5	APC 13x6.5 / Wood Prop 13*7	1120	5600	190	1400-5500
GC4250-800	800	3-5	5	APC 13x7 / Wood Prop 13*8	1250	5600	190	1400-5500
GC4260-710	710	3-5	5	APC 14x7 / Wood Prop 14x8	1650	7600	265	2700-7500