

GS - trójfazowe silniki klasy A/B/C

Typ silnika	RMP/V obroty/ V	Zakres napięcia [V]	Średnica wału [mm]	Zalecane śmigło	Maksymalny pobór prądu [A]	Maksymalna moc [W]	Maksymalny ciąg [g]	Masa silnika [g]	Masa modelu szybowiec [g]	Masa modelu sport [g]	Masa modelu - acro [g]
GA2826/1250	1250	6-20	3	GWS 8x4/ APC 9x4.7	18	180	800	41			
GA2830/1100	1100	6-20	3	APC 10x4.7/11x3.8	25	220	1050	52			
GA2830/910	910	6-20	3	APC 10x6/11x5	20	220	1050	52			
GA3530/1300	1300	6-20	4	APC 10x4/11x5/13x5	35	400	1700	67			
GA3530/950	950	6-20	4	APC 10x6/9x5/10x5	25	380	1400	67			
GB2433/3250	3250	7-18	3		18	315		65			
GB2445/3350	3350	7-15	3		34	450		97			
GB2835/2650	2650	10-24	4		33	620		98			
GC2220/1780	1780	7-12	2	GWS 8x4.3/8x4	12	120	600	28	500	400	200
GC2826/1260	1260	7-12	3,175	GWS 8x4 /PC 9x4.7	20	220	600	45	500	400	250
GC2826/1450	1450	7-12	3,175	GWS 8x5 /APC 7x4	24	240	600	45	500	400	250
GC2830/700	700	7-15	3,175	APC 10x4.7/11x3.8	17	220	900	57	800	600	400
GC2830/910	910	7-15	3,175	APC 10x4.7/10x5	21	260	900	57	800	600	400
GC2834/1120	1120	7-15	3,175	APC 10x5/9x4.5/10x4.7	26	380	1200	67	1100	800	550
GC2834/880	880	7-18	3,175	APC 11x5.5/12x6	22	340	1200	67	1100	800	550
GC3530/1330	1330	7-15	4	APC 10x5/9x4.5/10x4.7	35	350	1500	78	1400	1000	750
GC3530/950	950	7-15	4	APC 11x5.5/12x6	30	310	1500	78	1400	1000	750
GC3536/1250	1250	7-15	4	APC 11x5.5	50	680	2600	109	2500	2000	1400
GC3542/1100	1100	7-15	4	APC 11x7/11x3.8/12x6	65	850	2600	132	2500	2000	1400
GC3542/810	810	7-15	4	APC 12x6	45	660	2600	132	2500	2000	1400
GC3542/930	930	7-15	4	APC 11x5 10*5	55	750	2600	132	2500	2000	1400
GC4250/720	720	10-20	5	APC 13x6.5/Wood Prop	60	1120	5600	190	5500	2000	1400
GC4250/800	800	10-20	5	APC 13x7/Wood Prop	70	1250	5600	190	5500	2000	1400
GC4260/710	710	10-20	5	APC 14x7/Wood Prop	85	1650	7600	265	7500	4000	2700